

[illegible]

Current/phase	5.0 A
Voltage	2 V
DC Resistance/phase $\pm 10\%$	0.5 Ω
Inductance/phase $\pm 20\%$	2.0 mH
Holding torque	2.3 N • M
Inertia	0.48 kg • cm ²
Weight	13 kg
Encoder resolution	1000 cpr

PIN	1	2	3	11	12	13
颜色	黑	红	白	黄	绿	蓝
定义	A+	VCC	GND	B+	B-	A-

A+ 黑 Black
A- 红 Red

The diagram shows a vertical spring scale. A coiled spring is attached to a horizontal support at the top. A mass, represented by a circle with the letter 'M' inside, is suspended from the bottom of the spring.

B+ 黄 Yellow B- 绿 Green

设计	日期	材料	深圳市雷赛智能控制股份有限公司 SHENZHEN LEADSHINE TECHNOLOGY CO., LTD.			
Designed	Date	Material				
审核			第一角画法 First Angle projection		名称 Title	
Checked					混合伺服电机	
批准			重量 Weight	比例 Scale	请标注 Stage Mark	57HSM23-E1
Approved						
制 图 人 No.			共 1 张 第 1 张	Sheet 1 of 1	图号 DWG. NO.	LS-HSM57-03-0010-01